

MEMOLUB® Positive Displacement Lubricators

MEMOLUB® One 10 bar

- Single Point
- 10 bar pressure
- Remotely installed up to 2 meters
- 4 settings (1 month to 12 months)

Its reliability makes it the best performing mono-point lubricator in the market.

It is designed to work under extreme conditions such as in the mineral, cement or metal industries. It is ideal for applications where over-lubrication is necessary in order to protect the bearing against the external environment.

Most economical device in the market. The ONE is easily refilled by simply replacing the grease cartridge and battery pack. The ONE has a limited impact on the environment.

ONE
4 SETTINGS



Technical Specifications	
Cartridge Capacity	240cc
Maximum stroke pressure	10 bar / 140 psi
Batteries	4.5V Alkaline Battery
Remote Installation	Up to 2 meters – Ø 8mm tubing
Lubricants	Oil and grease (up to NLGI 2with an oil base between 100 and 460cSt)
Operating Temperature	-15°C to 50°C
Connections	¼ BSP

MEMO Adjustments	○	○	○	○
Adjustments	1 year	6 months	3 months	1 month
Average Daily Output	7.2 cc/day	7.2 cc/day	7.2 cc/day	7.2 cc/day

Product Ordering	
Product	Part Code
Memolub One	MEMO-1